



- diagonal impeller with stator
- Plastic housing
- 3-step or speed controllable
- integrated thermal switch
- including mounting bracket

### 230V 50Hz

Operating Point			1	2	3	4	5
Current	I	A	0.34	0.34	0.39	0.47	0.50
Power Consumption	P <sub>1</sub>	W	75	75	85	105	110
RPM	n	1/min	2870	2870	2820	2760	2730
SPL inlet	L <sub>WA5</sub>	dB (A)	-	73	72	72	73
SPL outlet	L <sub>WA6</sub>	dB (A)	-	76	75	77	78
SPL casing break out	L <sub>WA2</sub>	dB (A)	-	62	61	61	63

Voltage	U <sub>N</sub>	230V ~	Speed Control	3-2-1
Current	I <sub>N</sub>	0.5 A	Motor Protection	TAI
Current	I <sub>max</sub>	0.5 A	Capacitor	3,5 µF / 450 V
Ambient Temperature	t <sub>U</sub>	60 °C	Isolation Class	F
Medium Temperature	t <sub>F</sub>	60 °C	Poles	2
			Weight	0 kg

### Accessories for EL 200 E2M 01

For more information see internet

- TEE 015  
5-Step Transformer  
Without motor protection
- TES 0145  
7-Step Transformer  
without motor protection
- GS 03  
Isolator Switch
- VM 200  
Fast Clamps  
for noise reduction and sealing
- RSK 200  
Back Draught Shutter
- RSK 200D  
Back Draught Shutter  
with seal
- SG 200 01  
Protection Grille
- SG 200 02  
Protection Grille
- SDS 200  
Duct Silencer, rigid
- SDF 200  
Duct Silencer, flexible
- FV 200  
Filter Box with Mat Filter G3
- FT 200  
Filter Box for Bag Filter  
Without filter

